

# Chautauqua Chemicals Company, Inc.

4743 Cramer Drive PO Box 100 Ashville, NY 14710 Tel: (716) 763-4114 Fax: (716) 763-3555 cchemco.com

# MC 454

Acid Cleaner Technical Data

#### **GENERAL DESCRIPTION**

**MC 454** is an acid cleaner for use in soak and ultrasonic wash systems. It will remove soils and light oxides from steel, zinc, aluminum and brass. It is safe on ferrous and nonferrous metals including aluminum.

#### **NORMAL USE**

This product is diluted with water before usage. Determine proper ratio based on the volume of the tank.

For light soil removal, mix MC 454 at 1 to 30 with water.

For heavy-duty soil removal, mix MC 454 at 1 to 10 with water.

Operation temperatures are 130° to 170° F.

#### **ADVANTAGES**

- 1. Water based cleaner.
- 2. Biodegradable.
- 3. General purpose product, useful over a wide range of applications.
- 4. Brightens brass and aluminum.
- 5. Excellent rinsability.

#### **NORMAL CONTROL**

**Analytical Method** (Equipment available from Chautauqua Chemicals Co.)

- 1. Take a sample of the **MC 454** solution from the bath with a beaker and allow to cool to room temperature.
- 2. Measure out 10 mL using a graduated cylinder.
- 3. Add 3 to 5 drops of phenolphthalein indicator.
- 4. Add dropwise 1.0N sodium hydroxide solution while counting the drops and swirling the solution.
- 5. Stop adding drops when color changes to a dark pink color.
- 6. Calculation: Percent Concentration of **MC 454** = drops of 1.0N NaOH x 0.357

## HANDLING AND SAFETY CONSIDERATIONS

Consult product Safety Data Sheet for handling considerations, hazard information, and first aid procedures.

## OTHER INFORMATION

No warranty, expressed or implied of merchantability fitness for a particular purpose or otherwise, is made. Buyer assumes all risk of use, storage and handling. Chautauqua Chemicals Company, Inc. shall not be made liable for any incidental or consequential damages arising directly or indirectly in connection with the purchase, storage, handling or disposal of this product.

TDS Number: 50609D Revision Date: June 29, 2015

