

# MC 610 LF

Process Detergent  
*Technical Data*

## GENERAL DESCRIPTION

**MC 610 LF** is a silicate-free medium-duty detergent for use in spray wash systems or where a low foam detergent is needed. **MC 610 LF** is safe on aluminum, steel, stainless steel and copper alloys.

**MC 610 LF** is excellent for removal of machining lubricants and oils.

## NORMAL USE

This product is diluted with water before usage. Determine volume of tank before diluting.

For light-duty soil removal, mix **MC 610 LF** at 3% to 5% with water.

For heavy-duty soil removal, mix **MC 610 LF** at 8% to 12% with water.

Operating temperatures are 130° to 170° F.

## ADVANTAGES

1. Water based cleaner.
2. Biodegradable.
3. Silicate free.
4. Useful over a wide range of applications and operating conditions.
5. Excellent rinsability.

## HANDLING AND SAFETY CONSIDERATIONS

Consult product Safety Data Sheet for handling considerations, hazard information, and first aid procedures.

## OTHER INFORMATION

*No warranty, expressed or implied of merchantability fitness for a particular purpose or otherwise, is made. Buyer assumes all risk of use, storage and handling. Chautauqua Chemicals Company, Inc. shall not be made liable for any incidental or consequential damages arising directly or indirectly in connection with the purchase, storage, handling or disposal of this product.*

TDS Number:  
Revision Date:

50617D  
May 18, 2015

